Deep Cycle Lithium Battery Lead Acid Replacement 24V 50AH 100AH Rechargeable

UN38.3,MSDS,UL,CB,BIS,PSE,GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE

Basic Information

- Place of Origin:
- Brand Name: XWELL

China

XW-LAR256120

7-10 working days

5000 pcs per month

MoneyGram

L/C, D/A, D/P, T/T, Western Union,

negotiable

Carton

120AH

50A

12.8V ≤10mΩ

8S And 2P

Prismatic Cell

- Certification:
- Model Number:
- Minimum Order Quantity: 1 pcs
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

Product Specification

- Battery Capacity:
- Battery Energy: 3072WH
- Battery Configuration:
- Cell Name:
- Max Charge Current:
- Nominal Voltage:
- DC Resistance:
- Terminal Type:
- Cover Sealing Type:
- Waterproof:
- Highlight:

F1 Connector Screw / Gel Sealing Optional IP65 Lithium Battery Lead Acid Replacement 24V, Lithium Battery Lead Acid Replacement 100AH,

Rechargeable deep cycle lead acid battery

Lead Acid Replacement Deep Cycle 24V 50AH 100AH 120AH Rechargeable Lifepo4 Lithium Battery

Lithium Battery Lead Acid Replacement Technical Features:

Longer Cycle Life: Offers up to 10 times longer cycle life than lead acid battery, reduce replacement cost and total cost. Lighter Weight: About 40% of the weight of a comparable lead acid battery.

Higher Power: Delivers twice power of lead acid battery, even high discharge rate, while maintaining high energy capacity. Wider Temperature Range: -20~60°C

Superior Safety: Lithium Iron Phosphate chemistry eliminates the risk of explosion or combustion due to high impact, overchaeging or short circuit situation.

Lithium Battery Replacement Lead-Acid Specification

Model	25.6V50Ah	25.6V100Ah	25.6V120Ah
Nominal Voltage	25.6V		
Nominal Capacity @25C	50AH	100AH	120AH
Nominal Energy @25°C	1280WH	2560WH	3072WH
Battery Cell Type	Prismatic 50Ah	Prismatic 100Ah	Prismatic 120Ah
Configuration(xSxP)	8S1P	8S2P	8S2P
Max.Continous Charge Current @25°C	7A	12A	50A
Max. Continous Discharge Current @25°C	7A	12A	50A
DC Resistance	≤10mΩ		
Full Charged Voltage	29.2V		
Discharge Cut-off Voltage	20V		
Operate Temperature Range	Charge: 0°C~55°C; Discharge: -20°C~60°C; Storage: -20°C~45°C		
Dimension (mm)	326x171x215mm	522x240x218mm	522x240x218mm
Weight(KG)	12.5KG	25KG	28KG
Teminal Type	F1 terminal Screw teminal		Screw teminal
Cover Sealing type	Screw / gel sealing optional		
Waterproof	IP65		
Cyde life	100% DOD Cycles @ 25xC 1C/1C: >2000 times80% DOD Cycles @ 25C 1C/1C: >6000 times50% DoD Cycles @ 25C, 1C/1C: >5000 times		
LCD Screen Display	Optional(Show voltage V,Power %)		
Bluetooth	Optional (Bluetooth with mobile APP)		
Series and Parallels Function	Available to make in series and parallels to get 24V, 36V, 48V		
Heating Function	Optional, Suitable for cold area application		

Why choose us?

Xwell is a national high-tech company focusing on lithium-ion battery packaging, design, production and sales. The company was established in June 2017 with a registered capital of 5 million yuan.

The company has passed ISO 9001:2015 quality management system certification ISO14001:2015 environmental management system certification, QC080000 hazardous substance management system certification. The products have passed CE, CQC, RoHS, UN38.3, BIS and other certifications.

We adhere to the continuous independent innovation ability, excellent development and design ability and reasonable business positioning to provide customers with solutions to meet their different product needs. The company's business scope covers household energy storage, outdoor energy storage power supply, commercial energy storage system, photovoltaic energy storage system, security, medical treatment, precision instruments, intelligent travel, artificial intelligence, electric tools, unmanned aerial vehicles, ships 3C consumer electronics and other new energy fields. With efficient management. Relying on efficient management, reasonable price and perfect techni- cal support, we strive to become a leader in the energy storage industry and creat high-quality energy storage products to bring users a better experience.



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.



sales@esslithiumbattery.com 📀 esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China